




CARTONMAT PP544 The Modular Case Packer



Type "Pick & Place"

CartonMat PP544 is a standalone Pick & Place case packing system. It receives products directly from the production line, groups them according to a predefined pattern, picks them with a specially designed gripper and top loads them into cases. It can be combined with an external case erector and case sealer to provide a complete case packing solution.

CartonMat PP544 features two servo axes and state-of-the-art gripper technology (mechanical, vacuum, magnetic or combination) which ensure high speed, fast changeovers and precise product handling.

Its modular design makes it ideal for sites with limited available space.

CartonMat PP544 is IoT ready and incorporates the latest technologies of Industry 4.0.

Benefits

Reliability / Safety / Minimum Maintenance

CartonMat PP544 incorporates our 30 years of engineering excellence and combines intelligent design, top quality materials and robust construction, providing high productivity and minimum downtime and maintenance requirements.

Flexibility / Productivity Assurance / Minimized Operational Cost

CartonMat PP544 is designed to handle various predefined products with quick changeovers. It secures maximum productivity and the reduction of operational costs.

Upgradability

CartonMat PP544 can easily be upgraded to cover new requirements, such as new products and patterns, checkweighing, QC, etc.







CARTONMAT PP544 The Modular Case Packer

5
C
0
cat
Ŭ
ÿ
U
ð
0
S
Ü
ch
U
Ū

Productivity	max 10 cycles per minute
Operation	Fully automatic, Cycle, Manual
Changeovers	max 10 min
Handled products	Pet bottles, Glass bottles, Cartons, Cans, Aerosols, Flat bottom bag
CASES TYPES & DIMENSIONS	
Minimum Case Size (LxWxH)	250 x 200 x 100 mm
Maximum Case Size (LxWxH)	500 x 400 x 400 mm
Case Type	RSC Carton, Display, Tray, Crate
MACHINE DESIGN	
Overall Dimensions (LxWxH)	3,500 x 2,000 x 2,600 mm (including infeed & outfeed conveyors)
Infeed Conveyor	Chain or Modular Conveyor Belt, Height (Products) 900 \pm 30 mm
Outfeed Conveyor	Roller Conveyor, Height (Cartons) 700 \pm 30 mm
CONTROL	
PLC	Siemens S7-300
HMI	Siemens KTP-700
Servo & Pneumatics	FESTO
SAFETY	
Safety System	Double Emergency Stop circuit, Door Interlocks, CE Certification
SUPPLY REQUIREMENTS	
Power Supply	3 x 32A / 400V - 50 Hz (3P + N + GND)
Air Supply	6 Bar
WARRANTY	
Full Coverage Warranty	1 Year - Unlimited Cycles



Zenon Automation SAICT 17, Agiou Athanassiou Str., 19002, Peania, Attica, Greece Tel: +30 210 6690900, Fax: +30 210 6640200 ZENON | marketing@zenon.gr | www.zenon-robotics.com

DISTRIBUTED BY: